Estimated Duration of the Reducing Environment at the Saltstone Facility











Dan Kaplan and Thong Hang

Question, Background, & Our Approach

- Question: How long will the Saltstone facility remain reducing, thereby immobilizing several key radionuclides, including ⁹⁹Tc?
- Background: Slag (waste product from smelting) is purposely added to Saltstone to make it a reducing formulation.

$$Tc^{VII}O_4^- + 3e^- + 4H^+ \rightarrow Tc^{IV}O_2 - 2H_2O$$

- Soil Kd $Tc^{VII}O_4^- = 0 \text{ mL/g}$
- Soil Kd Tc^{IV} = 4000 mL/g
- Approach: Reactive transport modeling based on a conceptual model from <u>lysimeter field study</u> and input values from <u>laboratory</u> measurements.



Saltstone Facility




- Facility been operating intermittently since 1990.
- 2 vaults: 12 cells + 6 cells, cell = 100 x 100 x 25 ft.
- Vaults are partially filled.
- Saltstone: ~47% LLW liquid + ~3% cement + ~25% fly ash + ~25% slag
- 99% radioactivity → glass HLW; 90% volume
 → Saltstone



2011 start Salt Waste Processing Facility




Blast Furnace Slag






Tc(VII) vs. Tc(IV) in the SRS Subsurface





2.5 Year Field-Lysimeter Study: Saltstone Slag





Chemistry in Reactive Transport Model

```
O + e- ↔ R
O = oxidizing agent
R = reducing agent
e- = electron
```

 $O_{2(aq)} + R_{slag(Saltstone)} \rightarrow RO_{2(Saltstone)}$

 $O_{2(aq)}$ = dissolved O_2 MEASURED


R_{slag(Saltstone)} = Saltstone reduction capacity


MEASURED

RO_{2(Saltstone)} = oxygenated Saltstone CALCULATED




Reduction Capacity






"Total Reduction Capacity"
Ce(VI) → Ce(III) in acidic environment
Angus & Glasser (1985)



"Surface Reduction Capacity"
Cr(VI) → Cr(III) @ pH 7
Lee & Batchelor (2003)




Hydrology in Reactive Transport Model






Simulation Results at 250,000 Years



Red = Reduced Blue = Oxidized (units: meq e-/g solid)



Consumption of Slag Reduction Potential by Oxygen in Infiltration Water



Governing equation for PORFLOW

$$\frac{\partial C_k}{\partial t} + \frac{\partial}{\partial x_i} (V_i C_k) = \frac{\partial}{\partial x_i} (D_{ij} \frac{\partial C_k}{\partial x_j}) + R_k$$

$$\frac{\partial C_{Sk}}{\partial t} = \frac{\partial}{\partial x_i} (D_{ij} \frac{\partial C_{Sk}}{\partial x_i}) + R_{Sk}$$

Governing equation for Lukens et al.

$$\frac{I_d}{I_{\rm tot}} = 1 - \exp \Bigl[- \Bigl(\frac{\mu_{\rm i}}{\sin \phi} + \frac{\mu_{\rm f}}{\sin \theta} \Bigr) d \Bigr]$$

$$d = \sqrt{\frac{8C_{\mathrm{O_2}}tD_{\mathrm{m(O_2)}}}{N_{\mathrm{m}}C_{\mathrm{red}}}}$$



Conclusion

Obtaining similar results by two extremely different sets of calculations & assumptions provided additional assurance to the conclusion that the Saltstone Facility will maintain its reducing environment for >10,000 years (WSRC-RP-2003-00362, Rev. 2; WSRC-RP-2005-01674).

